



Maxxi II™ 35

Wet/Dry Vacuum

- **Quality filtration** ensures superior performance and keeps the motor dry
- **Powerful motor** maximizes cleaning performance
- **Accessories** help tackle diverse cleaning challenges

The Maxxi II™ 35 wet/dry vacuum exceeds cleaning expectations with increased versatility, enhanced power and cost-efficient performance.

Flexible operation

The Maxxi II™ 35 delivers unprecedented cleaning flexibility. When dirt or dust is the primary issue, the Maxxi II-35 offers quality filtration and dust capture, in addition to crevice and dusting tools. Operators can also employ the Maxxi II-35 for wet applications.

Superior filtration

Featuring a unique filter system, the Maxxi II-35 offers one solution for both wet and dry filtration. Designed with three durable components, the filter completely seals entry to the motor, protecting the motor from dust, debris, water or other liquids. Once the job is complete, the filter can be easily lifted out of the vacuum for a simple rinse, then replaced and ready for the next job in a matter of minutes.

Easy operation

The Maxxi II-35 wet/dry vacuum offers simple and reliable operation. The lightweight design ensures easy transportation. For enhanced performance, the Maxxi II-35 offers a variety of standard accessories, ranging from hoses and wands to squeegees and dusting tools.



Trusted. Reliable. Efficient.

Clarke®

Specifications	Maxxi II™ 35
Model Number	107409095
Power	120 V / 60 Hz
Power Cord Length	50 ft (15 m)
Power PMAX	1,100 W
Suction Power End of Tube	220 W
Airflow	101 CFM (45 L/Sec)
Vacuum at Nozzle	72 in of H ₂ O (20 kPa)
Sound Pressure Level	81 dB A
Tank Capacity	9 gal (35 L)
Dust Bag Capacity (Dry)	4 gal (18 L)
Wet Filter Area	163 in ² (1,051 cm ²)
Cartridge Filter Area	321 in ² (2,070 cm ²)
Hose Length	6 ft (1.9 m)
Hose Inlet	~1.25 in (32 mm)
Length x Width x Height	19 in x 17 in x 29 in (46 cm x 42 cm x 73 cm)
Weight	25 lb (11.5 kg)
Tube Holder	included
Accessory Storage	included
Dual Filter System	included

Specifications are subject to change without notice.



Filter System

Unique filter system protects the motor from water, while ensuring complete wet and dry filtration. It is designed with the following components:

- Dry cartridge filter keeps water away from the motor and is waterproof and washable for increased durability
- Red panel holds floater and prevents water overflow
- Blue panel mesh wet filter dissipates foam and is the first dust filter



Motor Head

Hinged-motor head quickly lifts off for easy service.



Accessories

The Maxxi II-35 features a variety of standard and optional accessories, including: hose, wand, squeegee floor tool, brush floor tool, crevice tool and dusting tool.

Applications

- Schools and Universities
- Hospitals/Healthcare Facilities
- Grocery Stores
- Retail Outlets
- Arenas and Stadiums
- Automobile Dealerships

Accessories

- Floor Nozzle Rubber Strip
- Floor Nozzle Brush Tool
- Crevice Tool
- Extension Tube/Wand
- Hose
- Cartridge Filter
- Wet Filter
- Tubeholder

Clarke®

9435 Winnetka Avenue North
Brooklyn Park, MN 55445
Phone: 800.253.0367
Fax: 800.825.2753
www.clarkeus.com

240 Superior Boulevard
Mississauga, Ontario, Canada L5T 2L2
Phone: 800.668.8400
Fax: 800.263.5111
www.nilfisk-advance.ca